

SuperLite[®] 17B Helmet Operations and Maintenance Manual

KMDSI Part # 100-001



Kirby Morgan Dive Systems, Inc.

1430 Jason Way

Santa Maria, CA 93455, USA

Telephone (805) 928-7772, FAX (805) 928-0342

E-Mail: KMDSI@KirbyMorgan.com, Web Site:www.KirbyMorgan.com

Manual prepared by Marine Marketing and Consulting, Dive Lab, Inc., and KMDSI.

NOTE: This manual is the most current for the SuperLite[®] 17B Helmet. It is page dated October 2011. Future changes will be shown on page III and the changed pages will carry the date of change. Previous manuals may not reflect these updates.

WARNING

Diving with compressed breathing gas is a hazardous activity. Even if you do everything right there is always the danger that you may be killed or injured. No piece of diving equipment can prevent the possibility that you may be killed or injured any time you enter the water.

The SuperLite[®]-17A/B helmet is CE Approved and meets or exceeds all performance and testing requirements of all government and non-government testing agencies throughout the world. It is approved for use on all commercial and military work underwater.

Kirby Morgan, SuperLite[®], BandMask, Band Mask, KMB, KMB-Band Mask, DSI, Diving Systems International, EXO, REX, SuperFlow[®] and DECA are all registered trademarks of Kirby Morgan Dive Systems, Inc. **Use of these terms to describe products that are not manufactured by KMDSI is illegal.**

The two dimensional images (such as photographs and illustrations) of our products are © copyrighted and trademarks of Kirby Morgan Dive Systems, Inc. The three dimensional forms of our products are trademark, trade design and trade dress protected.

© Copyright 1970-2011 Kirby Morgan Dive Systems, Inc. All rights reserved. This manual is made available for the express use of the owner of this Kirby Morgan product. No part of this manual may be reproduced, stored in any retrieval system, or transmitted, or used in any form or by any means, whether graphic, electronic, mechanical, photocopy, or otherwise by technology known or unknown, without the prior written permission of Kirby Morgan Dive Systems, Inc.

Warranty Information

Kirby Morgan Dive Systems, Inc. warrants every new mask, helmet, or KMACS 5 Air Control System to be free from defects in workmanship for a period of three hundred sixty five (365) days from date of purchase. This warranty covers all metal, fiberglass, and plastic parts. This warranty does NOT cover rubber parts, communications components, or head cushions. In addition, due to the electrolytic nature of underwater cutting and welding, chrome plating cannot be warranted when the diver engages in these activities.

Should any part become defective, contact the nearest authorized KMDSI dealer. If there is no dealer in your area, contact KMDSI directly at (805) 928-7772 x 229. You must have a return authorization from KMDSI prior to the return of any item, Upon approval from KMDSI, return the defective part, freight prepaid, to the KMDSI plant. The part will be repaired or replaced at no charge as deemed necessary by KMDSI.

This warranty becomes null and void if:

- 1) The product is not registered with KMDSI within ten (10) days of purchase.**
- 2) The product has not been properly serviced and/or maintained according to the appropriate KMDSI manual. In addition, the user is responsible to ensure that all product updates as recommended by KMDSI have been performed.**
- 3) Unauthorized modifications have been made to the product.**
- 4) The product has been abused or subjected to conditions which are unusual or exceed the product's intended service.**

NOTE: Be sure to complete the enclosed warranty card and return it to KMDSI immediately. No warranty claims will be honored without a satisfactorily completed warranty card on file at KMDSI.

Record Of Changes

It is the responsibility of the owner of this product to register their ownership with Kirby Morgan Dive Systems, Inc., by sending the warranty card provided. This card is to establish registration for any necessary warranty work and as a means of communication that allows KMDSI to contact the user regarding this product. The user must notify KMDSI of any change of address by the user or sale of the product.

All changes or revisions to this manual must be recorded in this document to ensure that the manual is up to date. Quantities marked in parenthesis.

Change Number	Date	Description of Change
1	05/28/2008	<p>Reworded: 2.1 Product Specifications, 2.4 Operational Specifications & Limitations, Warnings Corrected, 7.12.1 to the correct 7.16.1 and Table of Contents Updated.</p> <p>Added: Appendix A2, 3 and 4</p> <p>Moved: 2.4 Operational Specifications & Limitations, The SuperFlow® Demand Regulator Image Rotated and Scaled to fit.</p> <p>Removed: Table 1 and Table 2 from chapter 2.</p>
2	08/20/2008	<p>Page III Removed page number column.</p> <p>Page 16 First paragraph Part number added to Hard Shell.</p> <p>Page 17 Second paragraph 77 added to list of helmets.</p> <p>Chapter 1 rearranged and CE text added to KM-77 description.</p> <p>Pg 63 and 64 Chapter 5 made to two columns format and font changed to lower case instead of all caps.</p> <p>Page 65 Added Whisker Clamp Replacement Kit: Part # 525-032.</p> <p>Page 66 Corrected text to read "SL 17" instead of "KM 37 and 57" in 6.2, last sentence and photo caption.</p> <p>Page 102 step 17 corrected, "sssembly" to read "assembly."</p> <p>Page 173 Torque Specification corrections.</p> <p>Page 174 Added note about thread locking compound.</p>
3	03/13/2009	<p>Page 75: Space added between 6.5.1 Quad.</p> <p>Page 77: Removed grammatical error beneath image.</p> <p>Page 81: Corrected 40 inch pounds to 35 inch pounds in step 3. Lacquer thinner changed to acetone.</p> <p>Page 82: Corrected 40 inch pounds to 15 inch pounds in step 6. Lacquer thinner changed to acetone.</p> <p>Page 95: Corrected amount omitted inch pounds to 40 inch pounds in step 6.</p> <p>Page 105: Corrected 75 inch pounds to 100 inch pounds twice in step 18. Corrected 30 inch pounds to 40 inch pounds in step 22.</p> <p>Page 120: Corrected 75 inch pounds to 100 inch pounds in step 4.</p> <p>Page 122: Corrected 75 inch pounds to 100 inch pounds in step 8. Corrected 35 inch pounds to 40 inch pounds in step 9.</p> <p>Page 124: Removed step 11 and merged SPECIAL CARE text with step 10. Corrected 75 inch pounds to 100 inch pounds in step 16.</p> <p>Page 136: Corrected 35 inch pounds to 20 inch pounds in step 4.</p> <p>Page 140: Corrected 30 inch pounds to 20 inch pounds in step 3.</p> <p>Page 143: Corrected 35 inch pounds to 35-50 inch pounds in step 1.</p> <p>Page 152: Corrected 15 inch pounds to 20 inch pounds in step 5.</p>

Change Number	Date	Description of Change
3 (Continued)	03/13/2009	Page 154: Corrected 35 inch pounds to 25 inch pounds in step 5. Grammatical error, "reuse" corrected to reuse in step 7. Corrected 35 inch pounds to 20 inch pounds in step 1 of section 8.10.1.2. Corrected 35 inch pounds to 20 inch pounds in step 3 of section 8.10.1.2. Page 175: Location #94's part number corrected from 530-045 to 530-040. Added location #'s 6, 107 and 152a.
4	07/23/2009	CE material added
5	10/05/2009	Changed location # 82's part number from 550-372 to 550-038 in the torque specs.
6	11/06/2009	Chapter 2: addition of CE conforming criteria.
7	04/19/2010	Updated images and diagrams with new whiskers.
8	07/20/2010	Added wiring diagram to chapter 8.
9	04/06/2011	Updated earphones throughout manual
10	06/17/2011	Changed 61 meters to 67 meters in Appendix 3 Table 3 SuperFlow® 350 Regulator High Pressure Regulated Source
11	10/17/2011	Updated CE notifying body number from 0496 to 2049

 **WARNING**

Diving with compressed breathing gas is a hazardous activity. Even if you do everything right there is always the potential for serious injury or death. No one piece of diving equipment can prevent the possibility that you may be injured or killed any time you enter the water. We do not herein make any effort to teach the principles of diving. The information in this manual is intended for users of Kirby Morgan helmets and persons that maintain or service Kirby Morgan helmets.

Table Of Contents

Warranty Information.....	II
Record Of Changes	III
Definition of Signal Words Used in this Manual	XI
Chapter 1 General Information KMDSI Products.....	1
1.1 Introduction.....	1
1.2 Full-Face Masks and Manifolds.....	2
1.3 Kirby Morgan Diving Helmets.....	4
Chapter 2 Description & Operational Specifications - SuperLite®-17B ..	9
2.1 CR Marking	9
2.2 CE Certification.....	9
2.2.1. CE Marking	9
2.2.2. Notified Body	10
2.3 Product Specifications.....	10
2.4 Regulator Performance	10
2.5 Cage Code	10
2.6 Operational Specifications & Limitations	10
2.7 Helmet Features.....	11
2.8 General Description	13
2.8.1 Helmet Shell	13
2.8.2 Gas Flow Systems.....	13
2.8.3 Emergency Gas Supply System (EGS).....	18
2.8.4 Helmet Attachment to the Diver.....	18
2.8.5 Sealing Arrangement	18
2.8.6 Reducing Carbon Dioxide	19
2.8.7 Communications.....	20
2.8.8 Equalizing the Middle Ear.....	20
2.8.9 Face Port or Viewing Lens.....	21
2.8.10 Latch Catch Assembly, Pull Pin.....	21
2.9 Accessories.....	21
2.9.1 Eye Protection for Welding.....	21
2.9.2 Hot Water Shroud.....	22
2.9.3 Special Regulator Tools.....	22
2.10 Helmet Transport And Storage	23
2.10.1 Helmet Carrying Bag	24
2.11 Use of Kirby Morgan Original Replacement Parts.....	24
Chapter 3 Operating Instructions.....	25
3.1 Introduction.....	25
3.2 Design Purpose.....	25
3.3 First Use of Your Kirby Morgan Diving Helmet	27
3.4 Initial Adjustments to Your Helmet.....	27
3.4.1 Head Cushion	27
3.4.2 Adjusting the Neck Dam	28
3.5 Pre Dress-In Procedure.....	29

3.5.1 Pre-Dive Visual Inspection	29
3.6 Preparing the Helmet for Diving	30
3.6.1 Clean Face Port	30
3.6.2 Check Moving Parts	30
3.6.3 Check Communications	30
3.6.4 One-Way Valve Check	30
3) You can also test the one-way valve by opening the steady-flow valve and attempting to suck air back through the one-way valve. This is also a good way to test.	30
3.7 Emergency Gas System (EGS)	31
3.8 Setting Up to Dive	35
3.8.1 Flushing Out the Umbilical	35
3.8.2 Connecting the Umbilical to the Helmet	35
3.8.3 Opening the Breathing Gas Supply to the Helmet	36
3.8.4 Fogging Prevention	36
3.8.5 Donning The SuperLite®-17B	37
3.8.6 Testing the Breathing System	42
3.8.7 Sealing Integrity Check	42
3.9 Diving Procedures	43
3.9.1 Standing By to Dive	43
3.9.2 Attaching the Umbilical to the Harness	43
3.9.3 Diver Dons Helmet	43
3.9.4 Diver Check Gas Flow Systems	43
3.9.5 Communications Check	43
3.9.6 Diver Ready	43
3.9.7 Water Entry and Descent	44
3.10 Emergency Procedures	44
3.10.1 Flooding	44
3.10.2 Inhalation Resistance	44
3.10.3 Gas Flow Stops	44
3.10.4 Demand Regulator Free Flow	45
3.11 Post Dive Procedures	45
3.11.1 Removing the Equipment	45
3.11.2 Removing the Helmet	45
3.11.3 Storage of the Helmet Between Dives	46
Chapter 4 Troubleshooting	47
4.1 General	47
4.2 Communication Malfunction	47
4.3 One Way Valve Malfunction	47
4.4 Side Valve Malfunction	48
4.5 Water Leakage Into Helmet	48
4.6 Demand Regulator Malfunction	49
4.7 Emergency Gas Supply Valve	49
Chapter 5 Inspection and Maintenance	51
5.1 Routine Maintenance	51
5.1.1 Daily Pre-Dive Maintenance A2.3	51
5.1.2 Daily Post Dive Maintenance A2.6	51
5.1.3 Supervisors Equipment Checks A2.4 and A2.5	51

5.2 Monthly Maintenance	51
5.3 Yearly Maintenance	51
5.3.1 Overhaul/Inspection Checklist A2.1	51
Chapter 6 General Preventative Maintenance	53
6.1 Introduction	53
6.2 Required tools, Cleaning Agents, Lubrication	53
6.2.1 Component and Parts Cleaning	54
6.2.2 Component and Parts Lubrication	54
6.2.3 Teflon® Tape	55
6.2.4 RTV Sealant	55
6.2.5 Thread Locker	55
6.3 General Cleaning & Inspection Procedures	55
6.3.1 O-Ring Removal/Inspection/Cleaning and Lubrication	56
6.3.2 General Cleaning Guidelines	56
6.3.2.1 Mild Soap Solution for	57
General Cleaning and Leak Detector Use	57
6.3.2.2 Acidic Cleaning Solution and Procedures	57
6.3.2.3 Germicidal Cleaning Solutions and Procedure	57
6.4 Daily Maintenance	59
6.5 Monthly Inspections	61
6.5.1 Quad-Valve™ Exhaust System	61
6.5.2 Emergency Valve Assembly	62
6.5.3 Steady Flow/Defogger Valve	62
6.5.4 Bias Device Adjustable Section of Demand Regulator	62
6.5.5 Neck Clamp and Yoke Assembly	62
6.5.6 Latch Catch Mechanism	62
Chapter 7 Breathing System Maintenance and Repairs	63
7.1 Introduction	63
7.2 One Way Valve	63
7.2.1 Disassembly Of The One Way Valve	63
7.2.2 Reassembly of the One Way Valve	64
7.3 Side Block Assembly	65
7.3.1 General	65
7.3.2 Side Block Assembly Removal	65
7.3.3 Separating the Side Block Assembly from the Helmet Shell	66
7.3.4 Side Block Assembly Replacement	68
7.4 Defogger Valve	68
7.4.1 Disassembly of the Defogger Valve	69
7.4.2 Cleaning and Lubricating	69
7.4.3 Reassembly of the Defogger Valve	69
7.5 Emergency Valve Assembly	71
7.5.1 Disassembly of the Emergency Valve	71
7.5.2 Cleaning and Lubricating	71
7.5.3 Reassembly of Emergency Valve	72
7.5.4 Leak Testing the EGS Valve	73
7.6 Bent Tube Assembly	74
7.6.1 General	74

7.6.2 Removal of the Bent Tube Assembly.....	74
7.6.3 Inspection of Bent Tube Assembly.....	75
7.6.4 Installation of the Bent Tube Assembly.....	75
7.7 Hose Assembly (SL-17A only).....	76
7.7.1 Hose Assembly Removal.....	76
7.7.2 Hose Assembly Inspection “A” style Side Block.....	76
7.7.3 O-Ring Replacement.....	76
7.7.4 Hose Assembly Replacement.....	76
7.8.2 SuperFlow® Demand Regulator Test for Correct Adjustment, Fully Assembled.....	77
7.8 SuperFlow® Demand Regulator.....	77
7.8.1 General Regulator Information.....	77
7.8.3 Inspection of SuperFlow® Regulator Body Interior.....	78
7.8.4 SuperFlow® Demand Regulator Bias Adjustment Servicing, Demand Regulator on the Helmet.....	79
7.8.5 Reassembly of the SuperFlow® Regulator Adjustment System.....	80
7.8.6 SuperFlow® Demand Regulator Removal from Helmet.....	81
7.8.7 Disassembly of the SuperFlow® Demand Regulator.....	82
7.8.8 Inspection of SuperFlow® Demand Regulator Parts.....	85
7.8.9 Reassembly of the SuperFlow® 350 Demand Regulator.....	87
7.8.10 Tuning the SuperFlow® Regulator.....	91
7.8.10.1 Important Notes on Regulator Adjustment.....	92
7.8.11 SuperFlow® Regulator Steady Flows When Pressured Up: Special Tools Used.....	93
7.8.12 Regulator Steady Flows When Pressured Up.....	95
7.8.13 Regulator has Low or No Flow When Pressurized.....	95
7.8.14 Unexplained Demand Regulator Free Flow.....	95
7.9 Oral Nasal.....	96
7.9.1 Oral Nasal General Information.....	96
7.9.2 Oral Nasal Removal.....	96
7.9.3 Inspection of Oral Nasal.....	96
7.9.4 Oral Nasal Replacement.....	97
7.10 Quad-Valve™ Exhaust Assembly.....	98
7.10.1 Quad-Valve™ Assembly Removal.....	98
7.10.2 Quad-Valve™ Exhaust Valve Replacement.....	99
7.10.3 SuperFlow® Regulator Exhaust Valve Replacement.....	102
7.10.4 Quad-Valve™ Assembly Installation.....	103
7.11 Water Dump Exhaust Body.....	103
7.11.1 Water Dump Valve Removal.....	103
7.11.2 Water Dump Valve Replacement.....	103
7.11.3 Water Dump Valve Body Removal.....	103
7.11.4 Water Dump Valve Body Remounting.....	103
7.12 Reinstalling the Quad-Valve™ Exhaust Assembly.....	105
7.13 Standard Old Style Single Exhaust Whisker PN# 510-554.....	106
7.13.1 Whisker Removal.....	106
7.13.2 Reinstalling the Whisker.....	107
7.14 Double Exhaust Whisker.....	108
7.14.1 Double Exhaust Whisker Cleaning and Overhaul, Whisker PN# 525-102.....	108
7.15 Tri-Valve Exhaust Whisker.....	110

7.15.1 Demand Regulator Assembly Removal	110
7.15.2 Replacing the Regulator Exhaust Valve	110
7.15.3 Tri-Valve Exhaust Valve Replacement	111
7.15.4 Installing the Tri-Valve Exhaust System onto the Regulator	113
7.16 Overpressure Relief / Bleed Valve Overhaul Procedures	114
7.12.1 Overpressure Relief Valve	114
7.16.2 Overpressure Relief Valve Disassembly and Cleaning	114
7.16.3 Overpressure Relief Valve Reassembly	115
7.16.4 Overpressure Relief Valve Lift Check/Setting	115
Chapter 8 Corrective Maintenance	117
8.1 General	117
8.2 Yoke/Neck Clamp Assembly and Helmet Shell Inspection	117
8.3 Nose Block Assembly	119
8.3.1 Nose Block Assembly Removal	119
8.3.2 Nose Block Device Replacement	120
8.4 Handle and Weights	121
8.4.1 Handle Removal	121
8.4.2 Handle Replacement	122
8.4.3 Weight Removal	123
8.4.4 Weight Replacement	123
8.5 Chin Strap and Yoke Strap	125
8.5.1 Chin Strap Removal	125
8.5.2 Chin Strap Replacement	125
8.5.3 Removal of the Yoke Strap	126
8.5.4 Replacement of the Yoke Strap	126
8.6 Alignment Sleeve	128
8.6.1 Sleeve Removal and Inspection	128
8.6.2 Sleeve Replacement	128
8.7 Port Retainer	129
8.8 Face Port	129
8.8.1 General	129
8.8.2 Face Port and Nose Block Device Removal	129
8.8.3 Face Port and Nose Block Replacement	130
8.8.4 Special Note Regarding Ports	132
8.9 Communications System	133
8.9.1 General	133
8.9.2 Earphone Inspection	133
8.9.3 Microphone Removal and Replacement	134
8.9.4 Earphone Removal and Replacement	135
8.9.5 Waterproof Connector	135
8.9.5.1 Connector Removal	135
8.9.5.2 Connector Replacement	136
8.9.6 Communications Posts	137
8.9.6.1 Communications Post Removal	137
8.9.6.2 Communications Post Replacement	137
8.10 Neck Clamp/Yoke Assembly	138
8.10.1 Yoke	138

8.10.1.1 Yoke Removal and Disassembly	138
8.10.1.2 Yoke Replacement and Reassembly	140
8.10.2 Latch Catch Assembly	140
8.10.2.1 Latch Catch Mechanism Disassembly	140
8.10.2.2 Latch Catch Mechanism Reassembly	141
8.10.3 Neck Clamp Assembly	141
8.10.3.1 Neck Clamp Assembly Adjustment /Inspection	141
8.10.4 Neck Dam	143
8.10.4.1 Neck Dam Replacement	143
Pre-84 and Cold Water Type Neck Dam	144
Installation	144
8.10.4.2 Four Hole Method of Attaching Neck Dam to Hinge Tab	145
8.10.4.3 Patch Method of Attaching Neck Dam to Hinge Tab	146
8.10.4.4 Drawstring Type Neck Dam Installation	146
8.11 O-Ring Seal Replacement	148
8.12 Head Cushion Foam Replacement	148
Chapter 9 Accessories	149
9.1 Introduction	149
9.2 Hot Water Shroud General	149
9.2.1 Installation of the Hot Water Shroud	149
9.3 Low Pressure Inflator Hose Installation on the B Sideblock	151
9.4 Weld Lens & Weld Shield Assemblies	152
9.5 Use of Quick Disconnect	154
9.6 Double Exhaust System	155
9.6.1 Double Exhaust Kit Installation	155
Table of Equivalents	159
Appendix 1: Torque Specifications	160
Note on Torque Specifications	161
Checklist, Maintenance, and Pre-Dive Inspections	161
Appendix A2 Maintenance and Inspection Procedures	162
Appendix 3 Supply Pressure Requirements & Tables	164
Appendix 3 Table 1 Work Rate Expressed as Respiratory Minute Volume (RMV)*	165
Appendix 3 Table 2 Compressor Supply Table SuperFlow® and SuperFlow® 350	165
Appendix 3 Table 3 SuperFlow® 350 Regulator High Pressure Regulated Source	167
Appendix 4 Standard Kirby Morgan Surface Supply Pressure Formula - Old Method	167

Definition of Signal Words Used in this Manual

For your protection, pay particular attention to items identified by signal words in this manual. These terms are identified as, CAUTION, WARNING AND DANGER. It is especially important for you to read and understand these sections.

DANGER

This word indicates an imminently hazardous situation, which if not avoided, could result in death or serious injury.

WARNING

This word indicates a potentially hazardous situation, which, if not avoided, could result in death or serious injury.

CAUTION

This word indicates a potentially hazardous situation, which if not avoided, may result in minor or moderate injury. It may also be used to alert against unsafe practices.

If English is not your native language and you have any difficulty understanding the language of any warnings as they appear in the manual, please have them translated.

WARNING

Este é um aviso importante. Queira mandá-lo traduzir.

WARNING

Este es un aviso importante. Sirvase mandario traducir.

WARNING

Quest è un avviso importante. Tradurlo.

WARNING

Ceci est important. Veuillez traduire.

WARNING

Diese Mitteilung ist wichtig. Bitte übersetzen lassen.

If you have any questions concerning this manual or the operation of your helmet, contact KMDSI (805) 928-7772 or by Email at info@KMDSI.com or Dive Lab Inc. (850) 235-2715 or at Divelab@aol.com

IMPORTANT: A word about this manual. We have tried to make this manual as comprehensive and factual as possible. We reserve the right, however, to make changes at any time, without notice, in prices, colors, materials, equipment, specifications, models and availability. Since some information may have been updated since the time of printing, please contact your local KMDSI dealer if you have any questions. Periodically KMDSI Operations and Maintenance Manuals are reviewed. Any updates/changes will be posted on the KMDSI website and may be downloaded for insertion/correction.

Important Safety Information: This SuperLite® 17B diving helmet is intended for use by trained divers who have successfully completed a recognized training course in surface supplied diving

! WARNING

Follow all the instructions in this manual carefully and heed all safety precautions. Improper use of this diving helmet could result in serious injury or death.

! WARNING

Kirby Morgan Dive Systems, Inc. (KMDSI) warns all divers who use Kirby Morgan diving helmets or masks to be sure to use only KMDSI original parts from a KMDSI authorized dealer. Although other parts, O-rings and fittings may appear to fit your Kirby Morgan diving helmet or mask, they may not be manufactured to the same standards maintained by KMDSI. The use of any parts other than KMDSI original parts may lead to equipment failure and accidents.

! WARNING

Diving in waters that are chemically, biologically, or radiologically contaminated is extremely hazardous. Although Kirby Morgan diving helmets may be adapted for use in some contaminated environments, special training, equipment, and procedures are necessary. Do not dive in a contaminated environment unless you have been thoroughly trained and equipped for this type of diving.

Read this manual before using or maintaining the helmet, even if you have experience with other diving helmets. **If you have purchased the helmet new from a dealer, be sure to send in the warranty registration card so we may keep you informed of any safety notices that affect this product.** If you resell or loan this helmet to another diver, be sure this manual accompanies the helmet and that the person reads and understands the manual. In addition to the manual a log book should be used to log all repairs, maintenance and use.

! WARNING

This helmet was completely checked and should be ready to dive as it was shipped from the factory. However, it is always the diver's responsibility to check all the components of the helmet prior to diving.

! WARNING

Diving is a life threatening occupation. Even if you do everything right you can still be killed or injured. None of the models of Kirby Morgan helmets or masks can prevent accidents, injuries or death due to improper training, poor-health, improper supervision, improper job requirements, improper maintenance or acts of God.

! WARNING

Any and all fiberglass repairs done to this helmet **MUST** be done by a KMDSI factory trained repair facility. Painting is not recommended by KMDSI. Furthermore, many diving companies will not allow painted helmets to be used because painting can mask previous fiberglass damage. KMDSI certified technicians are not responsible for certifying helmets free from damage during annual overhauls.

! WARNING

Helmet shells can be re-gel coated by authorized/certified KMDSI trained technicians that have received fiberglass training by KMDSI. Helmets that are to be painted for cosmetic purposes, should be first, certified free of fiberglass damage by an authorized KMDSI technician certified in fiberglass repair. A log entry should be made in the helmet log that the helmet was free of damage prior to painting. Keep in mind other KMDSI technicians can refuse to work on helmet shells that have previously been painted or repaired by non KMDSI certified persons.

This manual is supplied to the original purchaser of this helmet. If you have any questions about the use of the helmet or you need another copy of this manual, contact KMDSI or your nearest KMDSI dealer. It may also be downloaded free from the KMDSI website at www.KirbyMorgan.com.

! WARNING

KMDSI helmets and masks are intended for underwater use only and should only be used by qualified divers that have received proper training in the use of this type of equipment. KMDSI helmets and masks should not be used or worn without the appropriate life support systems, such as air or gas supplies and support personnel as described in this manual.

! WARNING

KMDSI helmets and masks should never be used for motor sport racing, aviation / space craft use, or for chemical warfare use. The helmet must never be used by persons in poor physical condition, by persons with previous head, neck, or back injuries which could be aggravated by its use. The helmet should not be used by persons under the influence of drugs or alcohol. Furthermore, infants, children, or persons under the age of 18 should never wear KMDSI helmets and masks. Failure to pay heed to the above could result in serious injury or death.

! WARNING

Do not use KMDSI masks or helmets in currents exceeding 3.0 knots Use in currents greater than 3 knots may allow water to enter the exhaust valve, possibly causing regulator flooding. This could lead to drowning.

! WARNING

Surface-supplied diving can be a strenuous activity. The SuperLite®-17B weighs approximately 30 lbs. KMDSI recommends that persons with a previous neck or back injury seek professional medical approval prior to engaging in surface supplied diving operations using the SuperLite®-17B. Use of the SuperLite®-17B with a pre-existing physical/ medical condition may result in death or serious injury.

If you have any questions regarding the use, maintenance, or operation of this helmet, contact KMDSI at (805) 928-7772, fax: (805) 928-0342, or e-mail: info@kirbymorgan.com.

Components requiring lubrication, should only be lubricated with oxygen compatible lubricants such as Christo-Lube®, Flourolube, or Krytox®. Lubricants must be used sparingly and should not be mixed with other lubricants.

The information contained in this manual is intended to aid the user in optimizing the performance of this helmet. The application of some of this information will depend on the diving situation and the use of associated equipment. Many countries have specific laws and rules regarding commercial diving. It is important for the user to understand the rules, regulations, and philosophy imposed by the governing, regulating bodies whenever using commercial diving equipment.

 **WARNING**

Never use the helmet without first completing all pre-dive maintenance and set up procedures. Failure to complete all pre-dive checks could result in helmet failure due to problems with the incorrect set-up of the equipment. This could lead to serious personal injury or death.

 **WARNING**

Always read the Material Safety Data Sheet (MSDS) for any chemical - adhesive, cleaning agent, or lubricant - used on your Kirby Morgan helmet. Some of these chemicals may cause serious bodily injury or death if used improperly or without the proper personal protective equipment.

Whenever KMDSI helmets or masks are used in European Countries, which have adopted the C.E. certification programs, they must only be used with C.E. certified components. Diving operations should only be conducted within the limits of the operational specifications, and in accordance with the rules and regulations established by the governing authority in the specific country or geographical location where the diving operations are being conducted. If you have any questions concerning this manual or the operation of your helmet, contact KMDSI (805) 928-7772 or at KMDSI@KirbyMorgan.com or Dive Lab Inc. (850) 235-2715 or at Divelab@aol.com